

Fixture Triomont XT - for toilet with top flush button

Low model with dual flush 6 or 3l

GUSTAVSBERG /
SMARTER BATHROOMS



Product features



- Low model for installation under window or shelf area
- Thin fixture, only 380 mm wide
- Load tested for 400 kg

Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB1921102024

8711778169067

Packaging

L: 400,00 x W: 900,00 x H: 150,00 mm.

Weight: 12,00 kg

Energy labeling and certifications

- Fixture in accordance with the standard SS 820200Tank in accordance with EN 14055Ready for AMA installation without any extra components (SE)



Villeroy & Boch Gustavsberg AB
har produkter anpassade
till Branschregler Saker
Vatteninstallation.



Assembling & Care

Mounted per included installation instructions. The height dimensions (1000 mm) of the drawing mean a seat height of 410-430 mm depending on the toilet model. Can when installed be adjusted up to 610-630 mm. Flexible bolt spacing for wall-mounted toilet installation, c-c 180 or 230 mm. With bolt spacing 180 c-c, all toilets from Gustavsberg and Villeroy & Boch fit.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com