Shower mixer New Nautic - thermostat

With pipe connection downwards, 40 cc



Product features

- Safe Touch reduces the heat on the front of the mixer
- Maintains even water temperature upon pressure and temperature changes
- Can be expanded with bathtub spout

Article number etc.

RSK-nr:	ART-nr:	EAN-nr:
	GB41202423	7391530081250

Packaging
L: 0,00 x W: 0,00 x H: 0,00 mm.
Weight: 0,00 kg

Energy labeling and certifications

- Complies with Safe Water installation requirements.

Denna produkt är anpassad till Branschregler Säker Vatteninstallation 2021:1. Leverantören garanterar produktens funktion om branschreglerna och monteringsanvisningarna följs.

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Dokumentet skapat den 2024-03-29

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com