

Washbasin mixer Nautic - wall mounted

150 mm spout, 160 c-c



Product features

ECO-
TAP/ENERGY-
SAVING



ECO-
TAP/WATER-
SAVING



- Energy class B, saves energy and water
- Adjustable comfort flow and comfort temperature
- Plugged connections for extra water outlets

Article number etc.

RSK-nr:

ART-nr:

GB41204252

EAN-nr:

7393792217842

Packaging

L: 225,00 x W: 117,00 x H: 183,00 mm.

Weight: 2,20 kg

Energy labeling and certifications

- Complies with Safe Water installation requirements
- Energy class B, 1.86 kWh



Villeroy & Boch Gustavsberg AB
har produkter anpassade
till Branschregler Saker
Vatteninstallation.



Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 70°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com