

Shower mixer Nautic

Outlet downward, 160 c-c

GUSTAVSBERG /
SMARTER BATHROOMS



Product features



- Safe Touch reduces the heat on the front of the faucet
- Maintains even water temperature upon pressure and temperature changes
- Can be expanded with bathtub spout

Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB41205304

7393792225489

Packaging

L: 365,00 x W: 105,00 x H: 75,00 mm.

Weight: 1,89 kg

Energy labeling and certifications

- Complies with Safe Water installation requirements.



Denna produkt  r anpassad till
Branschregler S ker Vatteninstallation
2021:1. Leverant ren garanterar
produktens funktion om branschreglerna
och monteringsanvisningarna f lj s.



CERTIFIERING
KONTROLL

RI
SE



Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com