

# Bathroom sink faucet Care

With elongated lever

GUSTAVSBERG /  
SMARTER BATHROOMS



## Product features

ECO-  
TAP/ENERGY-  
SAVING



ECO-  
START



- Energy class A, saves water and energy
- Eco-start, 17°C when lever straight forward
- Adjustable comfort flow and comfort temperature

## Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB41214047 64

7393792217637

Packaging

L: 290,00 x W: 290,00 x H: 75,00 mm.


Weight: 1,41 kg

## Energy labeling and certifications

- Complies with Safe Water installation requirementsEnergy class A, 1.41 kWh



Villeroy & Boch Gustavsberg AB  
har produkter anpassade  
till Branschregler Saker  
Vatteninstallation.



## Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

[www.gustavsberg.com](http://www.gustavsberg.com) / [info@gustavsberg.com](mailto:info@gustavsberg.com)