

Shower mixer Nautic - single-lever

Shower mixer with vacuum valve, 150 c-c



Product features

ECO-TAP/ENERGY-
SAVING



ECO-TAP/WATER-
SAVING



- With vacuum valve and non-return valves in inlet
- Adjustable comfort flow can be activated as needed
- Backflow protection per SS-EN 1717 [HD]

Article number etc.

RSK-nr:

ART-nr:

GB41214274

EAN-nr:

7393792217903

Packaging

L: 225,00 x W: 117,00 x H: 183,00 mm.

Weight: 2,20 kg

Energy labeling and certifications

- Complies with Safe Water installation requirements.



Villeroy & Boch Gustavsberg AB
har produkter anpassade
till Branschregler Saker
Vatteninstallation.



Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com