

# Wall-hung toilet Nautic 1522 - with cistern, Hygienic Flush

Dual flush 4/2L, without seat, C+



## Product features



- Low flush button with a neat design
- Space between tank and wall for easier cleaning
- With open, glazed flush edge for simplified cleaning

## Article number etc.

RSK-nr:

ART-nr:  
GB1115222R1304

EAN-nr:  
7391530067360

Packaging  
L: 900,00 x W: 380,00 x H: 900,00 mm.  
Weight: 34,00 kg

## Energy labeling and certifications

- The product follows AMA recommendations, SS-EN 33 dimensioning and SS-EN 997 function. Complies with Safe Water installation requirements. CE approved



## Assembling & Care

Mounted with bolts directly on the wall. Washers, bushings and nuts included (M12) but not bolts. Bolt projection from finished wall must be  $60 \pm 2$  mm. Rubber bellows for waste pipe connection included. See supplied installation instructions and mounting kit for each toilet. Triomont fixture for wall hung toilet and bidet RSK 382 57 56, is recommended for installation on weak walls. According to the AMA the seat height should be 450 mm which corresponds to 270 mm distance (centre-centre) between the existing floor and the centre of the drain.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

[www.gustavsberg.com](http://www.gustavsberg.com) / [info@gustavsberg.com](mailto:info@gustavsberg.com)