

Wall-hung toilet Nautic 1522 - with cistern, Hygienic Flush

Single flush 4L, standard seat

GUSTAVSBERG /
SMARTER BATHROOMS



Product features

Hygienic
flush



No room
for dirt



- Easy-to-clean and minimalistic design
- Space between tank and wall for easier cleaning
- With open, glazed flush edge for simplified cleaning

Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB111522401211

7391530069258


Packaging

L: 900,00 x W: 380,00 x H: 900,00 mm.

Weight: 35,00 kg

Energy labeling and certifications

- The product follows AMA recommendations, SS-EN 33 dimensioning and SS-EN 997 function. Complies with Safe Water installation requirements. CE approved



Assembling & Care

Mounted with bolts directly on the wall. Washers, bushings and nuts included (M12) but not bolts. Bolt projection from finished wall must be 60 ± 2 mm. Rubber bellows for waste pipe connection included. See supplied installation instructions and mounting kit for each toilet. Triomont fixture for wall hung toilet and bidet RSK 382 57 56, is recommended for installation on weak walls. According to the AMA the seat height should be 450 mm which corresponds to 270 mm distance (centre-centre) between the existing floor and the centre of the drain.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com