Wall-hung toilet Public 6622 - with cistern, Hygienic Flush

4 Litre, no seat, C+





Product features



- Durable stainless steel push button suitable for public environments
- Open flush edge for simplified cleaning
- Ceramicplus for quick and eco-friendly cleaning

Article number etc.

RSK-nr:	ART-nr:	EAN-nr:
	GB1166224R1503	7391530074993

Packaging
L: 900,00 x W: 360,00 x H: 900,00 mm.
Weight: 32,00 kg

Energy labeling and certifications

- The product follows AMA recommendations, SS-EN 33 dimensioning and SS-EN 997 functionComplies with Safe Water installation requirementsCE approved

Villeroy & Boch Gustavsberg AB har produkter anpassade till Branschregler Säker Vatteninstallation.

Assembling & Care

Mounted with bolts directly on the wall. Washers, bushings and nuts included (M12) but not bolts. Bolt projection from finished wall must be 60 ± 2mm. Rubber bellows for waste pipe connection included. See supplied installation instructions and mounting kit for each toilet. Triomont fixture for wall hung toilet and bidet RSK 382 57 56, is recommended for installation on weak walls. According to the AMA the seat height should be 450 mm which corresponds to 270 mm distance (centre-centre) between the existing floor and the centre of the drain.

Dokumentet skapat den 2024-03-28

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com