

Shower mixer Nautic - single-lever

GUSTAVSBERG /
SMARTER BATHROOMS



With shower connection downwards, 160 c-c



Product features

- Adjustable comfort flow can be activated as needed
- Adjustable max temperature for increased scald protection
- Can be adjusted for universal accessibility with extended lever

Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB41204014

7393792217699

Packaging

L: 230,00 x W: 185,00 x H: 115,00 mm.

Weight: 1,85 kg

Energy labeling and certifications


- Complies with Safe Water installation requirements.



Villeroy & Boch Gustavsberg AB
har produkter anpassade
till Branschregler Saker
Vatteninstallation.



CERTIFIERING
KONTROLL



Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com