

# Shower mixer New Nautic - Thermostat

Lead-free, outlet up & down, 150 c-c

GUSTAVSBERG /  
SMARTER BATHROOMS



## Product features



- Safe Touch reduces heat on the front of the faucet
- Contains less than 0.1% lead
- Can be complemented with bathtub spout

## Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB412123020

7391530076379


Packaging

L: 292,00 x W: 95,00 x H: 74,00 mm.

Weight: 1,83 kg

## Energy labeling and certifications

- The product is adapted to fulfil Safe Water Installation industry guidelines



## Assembling & Care

Mounted according to the instructions. Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

[www.gustavsberg.com](http://www.gustavsberg.com) / [info@gustavsberg.com](mailto:info@gustavsberg.com)