

Shower mixer Nautic - single-lever

With shower connection downwards, 150 c-c

GUSTAVSBERG /
SMARTER BATHROOMS



Product features

- Can be combined with all kitchen or bathroom spouts
- Adjustable comfort flow can be activated as needed
- Plugged connections for extra water outlets

Article number etc.

RSK-nr:

ART-nr:

EAN-nr:

GB41214004

7393792217682

Packaging

L: 230,00 x W: 165,00 x H: 115,00 mm.

Weight: 1,86 kg

Energy labeling and certifications

- Complies with Safe Water installation requirements.



Villeroy & Boch Gustavsberg AB
har produkter anpassade
till Branschregler Saker
Vatteninstallation.



Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 80°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Dokumentet skapat den 2024-04-29



Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com