
Washbasin mixer New Nautic - 150 mm

With side spray, wall bracket and shutoff valve





Product features

Quick fit

- Energy Class A
- Cold-start, only cold water when the lever is in straight forward position
- Easy grip lever with clear colour marking for hot and cold

Article number etc.

RSK-nr:	ART-nr:	EAN-nr:
	GB41216185	7393792235075

Packaging
L: 290,00 x W: 290,00 x H: 75,00 mm.
Weight: 3,32 kg

Energy labeling and certifications

Denna produkt är anpassad till Branschregler Säker Vatteninstallation 2021:1. Leverantören garanterar produktens funktion om branschreglerna och monteringsanvisningarna följs.

Assembling & Care

Prior to installation the lines must be flushed up to the faucet. The faucet is connected with the cold water line on the right and the hot water line on the left. Water pressure: max 1000 kPa, min 50kPa. Hot water temperature: max 70°C, min 45°C. Please note that we are not liable for damage resulting from improper installation.

Dokumentet skapat den 2024-03-28

Villeroy & Boch Gustavsberg AB / Box 400, 134 29 Gustavsberg, Sweden / Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36 /

www.gustavsberg.com / info@gustavsberg.com